

MT15 Series

Zoomable light
M15-SP0001



The luminous effect can be adjusted by rotating the lamp

Quickinfo

GENERAL

Magnetic suction installation
IP20

LED

BRIDGELUX
3W
3000K, 3500K, 4000K
50000h@L80
CRI ≥ 90
SDCM < 3

OPTICAL

Direct illumination
Beam angle 24°/36°
Optical accessories

ELECTRICAL

ON/OFF,
Tuya Zigbee
0-10V,
Phase DIM,
DALI DIM
PHYSICAL
Aluminum




The installation of lighting is very easy, with Arcilux magnetic track, just click.
Adopting a modular concept, different lighting fixtures to match different spaces.
The number of lamps can be adjusted upon the actual needs.
Free movement and angle adjustment, increase the freedom of lighting design
safety voltage, No risk of electric shock

Physical photos



M15-SP0001 3W

Technical drawing



M15-SP0001 3W

Standard configuration

COLOUR TEMPERATURE

3000K
3500K
4000K

CONTROL

ON/OFF

COLOUR(housing)

Black
White

POWER	VOLTAGE	CCT	LUMINOUS FLUX
3W	85V/24V	3000K/3500K/4000K	420lm

LUMINOUS FLUX

1872lm
B, CRI 90, tolerance range of electrical and optical parameters: ±10%

Available Colors



White