



OONO ON 2 930 B



29614 9300 B

AVAILABLE IN

BLACK 29614 9300 B

GOLD COLOURED 29614 9300 GC

WHITE 29614 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP44/20
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	2.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2178lm // 17,2W // 127lm/W
LED TECHNICS (LUMINAIRE)	944lm // 19,8W // 48lm/W

Remarks

IP44 : wall mounted / IP20 : ceiling mounted

For detailed installation instructions, please consult the manual: [29614_XXX0_HAND.pdf](#)



OONO ON 2 930 B

29614 9300 B

Notes: