

Luminaire Specification



LS40HP

— LINE 40 series



[Basic Parameters]

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005), White (RAL9003), Champagne Gold , Rose Gold, Matt Green(RAL6019), Matt Orange(RAL2008) , Matt Yellow(RAL1004), Matt Blue(RAL5012)
- Length: 1200mm/1500mm /1800mm/2400mm optional
- IP grade: IP20
- CCT: 2700/3000/3500/4000/5000/6500/ 3000-6500K optional
- CRI: 80/90
- SDCM: <3 Step (ANSI)
- Beam angle: 60°x75°
- U G R: UGR≤19(X=4H,Y=8H)
- Light efficiency: 75 lm/W
- Input voltage: AC200-240V
- Lighting direction: downward
- Dimming method: Non / 1-10V / DALI+push optional
- Application: Indoor
- Certification: CE, UKCA, ROHS, Reach
- Warranty: 5 years(Emergency power version:3 years)



[Luminaire Parameters]

Version	Model	Length	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	Beam Angle (°)	CRI	CCT	Lumen (LM)
Normal/ Emergency	LS40HP	1200mm [3.94ft]	200-240 VAC	0.18 [0.05A/ft]	34.0 [8.63W/ft]	37.4 [9.49W/ft]	60°x75°	>80	2700K	2370 [600LM/ft]
									3000K	2425 [615LM/ft]
									3500K	2475 [630LM/ft]
									4000K	2550 [645LM/ft]
									5000K	2550 [645LM/ft]
									6500K	2550 [645LM/ft]
								>90	2700K	2040 [520LM/ft]
									3000K	2085 [530LM/ft]
									3500K	2125 [540LM/ft]
									4000K	2195 [555LM/ft]
									5000K	2195 [555LM/ft]
									6500K	2195 [555LM/ft]

Normal	LS40HP	1500mm [4.92ft]	200-240 VAC	0.24 [0.05A/ft]	46.0 [9.35W/ft]	50.6 [10.29W/ft]	60°x75°	>80	2700K	3210 [650LM/ft]
									3000K	3280 [665LM/ft]
									3500K	3345 [680LM/ft]
									4000K	3450 [700LM/ft]
									5000K	3450 [700LM/ft]
									6500K	3450 [700LM/ft]
		>90		2700K	2760 [560LM/ft]					
				3000K	2820 [575LM/ft]					
				3500K	2880 [585LM/ft]					
				4000K	2965 [605LM/ft]					
				5000K	2965 [605LM/ft]					
				6500K	2965 [605LM/ft]					
	>80	2700K		3555 [600LM/ft]						
		3000K		3635 [615LM/ft]						
		3500K		3710 [630LM/ft]						
		4000K		3825 [645LM/ft]						
		5000K		3825 [645LM/ft]						
		6500K		3825 [645LM/ft]						
	>90	2700K		3060 [520LM/ft]						
		3000K		3125 [530LM/ft]						
		3500K		3190 [540LM/ft]						
		4000K		3290 [555LM/ft]						
		5000K		3290 [555LM/ft]						
		6500K		3290 [555LM/ft]						
		2400mm [7.87ft]	0.35 [0.05A/ft]	68.0 [8.64W/ft]	74.8 [9.50W/ft]	>80	2700K	4745 [605LM/ft]		
							3000K	4845 [615LM/ft]		
							3500K	4945 [630LM/ft]		
							4000K	5100 [650LM/ft]		
							5000K	5100 [650LM/ft]		
							6500K	5100 [650LM/ft]		
	>90	2700K	4080 [520LM/ft]							
		3000K	4165 [530LM/ft]							
		3500K	4255 [540LM/ft]							
		4000K	4385 [555LM/ft]							
		5000K	4385 [555LM/ft]							
		6500K	4385 [555LM/ft]							


Dial switch CCT tunable	LS40FD	1200mm [3.94ft]	200-240 VAC	0.18 [0.05A/ft]	34.0 [8.63W/ft]	37.4 [9.49W/ft]	60°x75°	>80	3000K	2480 [630LM/ft]
									4300K	2585 [655LM/ft]
									6500K	2515 [640LM/ft]
				>90	3000K	2135 [540LM/ft]				
					4300K	2220 [565LM/ft]				
					6500K	2165 [550LM/ft]				
				>80	3000K	3360 [685LM/ft]				
					4300K	3495 [710LM/ft]				
					6500K	3405 [690LM/ft]				
				>90	3000K	2890 [585LM/ft]				
					4300K	3005 [610LM/ft]				
					6500K	2925 [595LM/ft]				
1800mm [5.91ft]		0.26 [0.05A/ft]	51.0 [8.63W/ft]	56.1 [9.49W/ft]	>80	3000K	3725 [630LM/ft]			
						4300K	3875 [655LM/ft]			
						6500K	3775 [640LM/ft]			
	>90	3000K	3200 [540LM/ft]							
		4300K	3335 [565LM/ft]							
		6500K	3245 [550LM/ft]							
2400mm [7.87ft]		0.35 [0.05A/ft]	68.0 [8.64W/ft]	74.8 [9.50W/ft]	>80	3000K	4965 [630LM/ft]			
						4300K	5170 [655LM/ft]			
						6500K	5030 [640LM/ft]			
	>90	3000K	4270 [540LM/ft]							
		4300K	4445 [565LM/ft]							
		6500K	4330 [550LM/ft]							

Note:


1. The output data is based on the testing result of Ra80,4000k,white luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value;
- 4.The luminous flux of black luminaire is 55% of white luminaire.

[Optical Parameter]

[Normal/Emergency]




Luminous intensity
distribution diagram




AAI Figure

[Dial switch CCT tunable]



Luminous intensity
distribution diagram



AAI Figure

[Product mechanical data]



1197.5mm
[47.14"]



83.0mm
[3.27"]
44.8mm
[1.76"]



1495.5mm
[58.88"]



1793.5mm
[70.61"]



2389.5mm
[94.07"]

Note:Luminaires length shown above indicates the length of profile + thickness of 2 end caps,
where each end cap is 2.5mm thick, 2 end caps is 5mm thick in total.

【Product Accessories Information】

Picture	Section size	Name	Description	Model	Note
		Splicing bar (external)	Size:L110*W15.5*H11.7mm [Inch size:L4.33"*W0.61"*H0.46"]	EX-41	Splicing accessories
		Splicing bar (internal)	Material:SPCC Size:L135*W41.4*H42.2mm [Inch size:L5.31"*W1.63"*H1.66"]	EX-46(N)	
	/	Pendant cable (with junction box)	Junction box L80*W80*H30mm [Inch Size:L3.15"*W3.15"*H1.18"] Steel cable D1.5*2000/4000mm [Inch Size: D0.06"*78.74"/157.48"]	PY-D	Pendant installation accessories
	/	Pendant cable	Steel cable D1.5*2000/4000mm [Inch Size: D0.06"*78.74"/157.48"]	PN-D	
		Track pendant rod	Material:Fe Size:φ13.5*(500/1000)mm [Inch size:φ0.53"*(19.69"/39.37")] Other:0.5-1.0/1.0-2.0M adjustable [19.69"-39.37"/39.37"-78.74"]	PG-I	
		Pendant installation clip	Material:PC Size:L31.6*W20mm*H5.8mm [Inch size:L1.24"*H0.79"*H0.23"]	CP-44	
	/	Surface mounted buckle	Size:L72*W54*H5.9mm (Inch Size:L2.83"*W2.13"*H0.23")	CL-08	Ceiling installation accessory
		L-shaped corner (60°)	Material:AL6063-T5 Size:L200*W173.2*H83.0mm [Inch size:L7.87"*W6.82"*H3.27"]	L60-LS40	Pendant / Ceiling standard corne
		L-shaped corner (90°)	Material:AL6063-T5 Size:L200*W200*H83.0mm [Inch size:L7.87"*W7.87"*H3.27"]	L90-LS40	
		L-shaped corner (120°)	Material:AL6063-T5 Size:L200*W195.6*H83.0mm [Inch size:L7.87"*W7.70"*H3.27"]	L120-LS40	
		Y-shaped corner	Material:AL6063-T5 Size:L368.8*W319.4*H83.0mm [Inch size:L14.52"*W12.57"*H3.27"]	Y120-LS40	
		X-shaped corner	Material:AL6063-T5 Size:L400*W400*H83.0mm [Inch size:L15.75"*W15.75"*H3.27"]	X90-LS40	

【Version Type】

【Normal】

- 75lm/W
- Dimming method: Non / 1-10V / DALI+push





【Dial switch CCT control】

- Dimming method: Non/ 1-10V/ DALI+push optional
- 3000K/4300K/6500K 3-tier CCT adjustable, can achieve general lighting demands




【Emergency model】

· Dimming method: Non / 1-10V / DALI+push optional




· Technical parameters:

- Input voltage: 220-240VAC/50-60Hz
- Input current/power: 50mA/4W
- Charging time: 24 hours
- Power(emergency mode): 4W constant power output
- Battery capacity: 7.4V 2500mAh
- Emergency time: ≥ 3 hours
- Emergency light efficiency: ≥ 75 LM/W



Indicator light introduction

- ① Green/flashing: Charging
- ② Green/on: Full-charged
- ③ Red/on: Discharging(emergency mode)
- ④ Red/flashing: Discharging(emergency mode) finished soon
- ⑤ Yellow/on: Error



Test switch introduction

Press the test switch to confirm whether the emergency function is normal

