

REC



MORE INFO >>

		P	CCT	I	Flux	LOR
REC Mini	A308-00- Ⓞ -0- WT NT PR	20W	2700K	700mA	2450 lm	75%
	A308-00- Ⓞ -1- WT NT PR	20W	3000K	700mA	2650 lm	75%
	A308-00- Ⓞ -2- WT NT PR	20W	4000K	700mA	2700 lm	75%

220
240 V~ |  IP20 | CRI>90 | L80B10
> 60.000 h



Ⓞ *OPTIONS

1	No DIM
2	DIM DALI
3	DIM Push



MORE INFO >>



		P	CCT	I	Flux	LOR
REC	A256-00- Ⓞ -0- WT NT PR	39,5W	2700K	400mA	5200 lm	85%
	A256-00- Ⓞ -1- WT NT PR	39,5W	3000K	400mA	5625 lm	85%
	A256-00- Ⓞ -2- WT NT PR	39,5W	4000K	400mA	5725 lm	85%

220
240 V~ |  IP20 | CRI>90 | L80B10
> 60.000 h



Ⓞ *OPTIONS

1	No DIM
2	DIM DALI Push



COLOUR | WT  | NT  | PR 

MATERIAL |  AL |  PMMA

RAL  » 328

PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

 » 304



MORE INFO >>

		P	CCT	I	Flux	LOR
REC Double Mini	A310-00- 0-0- WT NT PR	16,5W	2700K	500mA	2300 lm	72%
	A310-00- 0-1- WT NT PR	16,5W	3000K	500mA	2500 lm	72%
	A310-00- 0-2- WT NT PR	16,5W	4000K	500mA	2530 lm	72%

220
240 V~ |  IP20 | CRI>90 | L80B10
>60.000 h



00 *OPTIONS

1	No DIM
2	DIM DALI Push



MORE INFO >>

		P	CCT	I	Flux	LOR
REC Double	A309-00- 0-0- WT NT PR	29,5W	2700K	900mA	4150 lm	76%
	A309-00- 0-1- WT NT PR	29,5W	3000K	900mA	4500 lm	76%
	A309-00- 0-2- WT NT PR	29,5W	4000K	900mA	4560 lm	76%
REC Double Engine	A309-01- 0-0- WT NT PR	2 x 14,7W	2700K	2 x 450mA	2 x 2075 lm	76%
	A309-01- 0-1- WT NT PR	2 x 14,7W	3000K	2 x 450mA	2 x 2250 lm	76%
	A309-01- 0-2- WT NT PR	2 x 14,7W	4000K	2 x 450mA	2 x 2280 lm	76%


220
240 V~ |  IP20 | CRI>90 | L80B10
>60.000 h




00 *OPTIONS

1	No DIM
2	DIM DALI Push

REC DOUBLE MINI



REC DOUBLE



COLOUR | WT  | NT  | PR 

MATERIAL |  AL |  PMMA

RAL  » 328

PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

 » 304

REC



MORE INFO >>

		CCT	LOR
REC Micro	A461-00-00- WT NT PR	2700K	79%
	A461-00-01- WT NT PR	3000K	79%
	A461-00-02- WT NT PR	4000K	79%

III IP20 | CRI>90 | L80B10 >60.000 h



** DRIVER OPTIONS

	P	I	CCT	Flux
0434-00-40 1 to 2 Rec Micro	12,8W	700mA	2700K	1465 lm
			3000K	1560 lm
			4000K	1650 lm
0434-01-43 1 to 3 Rec Micro	12,8W	700mA	2700K	1465 lm
			3000K	1560 lm
			4000K	1650 lm
0434-00-46 1 to 2 Rec Micro	12,8W	700mA	2700K	1465 lm
			3000K	1560 lm
			4000K	1650 lm
0434-01-25 1 to 3 Rec Micro	12,8W	700mA	2700K	1465 lm
			3000K	1560 lm
			4000K	1650 lm

220 V~ | DRIVER MUST BE PLACED ON REMOTE
240 | DIM PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT

i » 296



MORE INFO >>

		P	CCT	I	Flux	LOR
REC Slim	A457-00- ② -0- WT NT PR	27W	2700K	700mA	3700 lm	86%
	A457-00- ② -1- WT NT PR	27W	3000K	700mA	3800 lm	86%
	A457-00- ② -2- WT NT PR	27W	4000K	700mA	4000 lm	86%


220 V~ | IP20 | CRI>90 | L80B10 >60.000 h




② *OPTIONS

1	No DIM
2	DIM DALI
3	DIM Push

REC Micro



REC Slim



COLOUR | WT □ | NT ■ | PR ■ |

MATERIAL | AL | PMMA |

RAL i » 328

PR: PRIMER COATING FINISHING
COLOURS MAY AFFECT THE LIGHTING PARAMETERS

(()) » 304