

Roma

220-240V AC dimmable (DALI/Push DIM)
A14817.036.0502



Data sheet

CODE	A14817.036.0502
SYSTEM POWER CONSUMPTION	19W
EFFICACY	74.53lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B10) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2280lm
LUMEN OUTPUT	1416lm
EFFICIENCY	62.1%
WEIGHT	7,34 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	28,0 x 77,0 x 30,0 cm



Wall lighting fixture for interiors, with direct light emission.
Structure made of milled aluminium with bronze polyacrylic paint and galvanised steel tie rods.
Pickled sheet metal wall mounting bracket.
Moulded and curved cathedral glass diffusers.
Outer covering structure in laser-cut and bent aluminium sheet and with bronze polyacrylic paint.

Technical drawing

